



**Main features**

- Automatic scan Com Port/Network
- Support firmware upgrade
- Support ExportConfig/ImportConfig
- Multiple country languages
- Global frequency(860~960MHz)
- Password mode
- Read specify tag
- Relay
- Data cache
- Multiple customizable communication protocols
- Remote listening
- RSSI

**Product technical parameter**

Frequency	865~868MHz (EU standard),902~928MHz (US standard)
Protocol	ISO18000-6B/6C(EPC GEN2)
Built-in antenna	9dbi circular antenna
Work mode	Active / trigger / answer / password mode(optional)
RF power	26dbm (adjustable)
Read distance	<b>8~10 m (depends on tag)</b>
Interface	RS232/WG26/RELAY/TCP/IP/POE/WIFI(optional)
Power supply	9~36V
Reader Size	260*260*60mm
Net weight	1.2kg
Package size	400*300*100mm
Package gross weight	2.3kg
Operating Temp	-10~+55 °C
Storage Temp	-20~+75 °C

**Detailed image**

01 Spare parts: 1pc power adapter,1pc plug,1pc installation bracket



02 Reader dimension:



03 Interface:

- Standard interface RS232/WG/Relay
- Optional interface TCP/IP/POE/USB/TTL/RS485/WIFI(optional)

Power		RS232			WG				Relay		
12V	GND	TX	RX	GND	D0	D1	GND	TGIN	NO	NC	COM
red	black	light green	yellow	pink	green	white	brown	blue	purple	orange	grey



04 Package:

- Package size:400\*300\*100mm
- Package weight: 2.3kg

